

PATENT ABSTRACTS OF JAPAN

(11)Publication number : **10-270776**

(43)Date of publication of application : **09.10.1998**

(51)Int.Cl.

H01L 43/12

C23C 14/34

G11B 5/39

H01F 41/18

(21)Application number : **09-071790**

(71)Applicant : **SANYO ELECTRIC CO LTD**

(22)Date of filing : **25.03.1997**

(72)Inventor : **UMEMOTO TAKUJI**

MAEDA ATSUSHI

TANUMA TOSHIO


KUME MINORU

(54) METHOD FOR MANUFACTURING MAGNETORESISTANCE EFFECT FILM

(57)Abstract:

PROBLEM TO BE SOLVED: To improve a magnetic field sensitivity by forming at least one magnetic layer of a multilayer film in an atmosphere containing a hydrogen gas by the sputtering method.

SOLUTION: A first ferromagnetic layer 3, a non-magnetic layer 4, and a second ferromagnetic layer 5 are sequentially formed. The coercive force of the first ferromagnetic layer 3 is smaller than the ferromagnetic layer 5. In this kind of coercive force difference type multilayer film, a first ferromagnetic layer 3 with a small coercive force becomes a free layer and its magnetization direction changes due to the influence of an external magnetic field. Therefore, in this kind of coercive force difference type multilayer film, at least the first ferromagnetic layer 3 of the multilayer film is formed by the sputtering method in an atmosphere containing a hydrogen gas, thus reducing the coercive force of the first ferromagnetic layer 3 and improving a magnetic field sensitivity.



LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]